

LISTING OF THE CLAIMS

A complete listing of the claims is provided below. This listing of claims will replace all prior versions and listings of claims in the application.

1. (Currently Amended) A dock leveler, comprising:

a base assembly;

a ramp assembly configured to rotate from a generally vertical stored position to one or more lowered operating positions, wherein the ramp assembly is pivotally coupled to said base assembly at a pivot point located generally at one end of the ramp assembly; and,

a counterbalance assembly comprising:

a first anchor point;

a second anchor point;

a flexible member at least one effective anchor point and,

a biasing member having a central longitudinal axis defining a line of action, wherein the biasing member is coupled at one end to the ramp assembly at said first anchor point and to the flexible member at an other end of the biasing member, and the flexible member is connected to the base assembly or a dock at the second anchor point, and wherein along the line of action, at least one effective anchor point is defined as a point on the line of action proximate to a contact point between the flexible member and a cam surface. between the first and second anchor point and which location relative to the pivot point changes as said ramp assembly rotates,

~~and further wherein as the at least one effective anchor point moves, the line of action of the biasing member moves to change counterbalance characteristics of the ramp assembly.~~

2. (Original) A dock leveler according to claim 1, wherein the biasing member is a spring.

3. (Cancelled)

4. (Cancelled)

5. (Currently Amended) A dock leveler according to claim [[3]] 1, wherein the flexible member is chosen from a chain, a cable, and a band.

6. (Original) A dock leveler according to claim 5, wherein the flexible member is a chain.

7. (Currently Amended) A dock leveler according to claim [[3]] 1, wherein the base assembly comprises a cam plate defining the cam surface and shaped to deflect the line of action as the ramp assembly rotates by selectively engaging the flexible member.

8. (Currently Amended) A dock leveler according to claim 7, wherein the biasing flexible member is coupled at the second anchor point to the base assembly.

9. (Original) A dock leveler according to claim 7, wherein the biasing member is a spring and the cam plate includes an anchor hole at which the spring is fixedly coupled to the base assembly via the flexible member, an upper cam surface having a shape, and a lower cam surface having a shape, wherein the upper cam surface, lower cam surface, anchor point, and flexible member cooperate to deflect the line of action as the ramp assembly rotates.

10. (Previously Presented) A dock leveler according to claim 9, wherein the ramp assembly has a weight moment and the shape of the lower cam surface is configured to provide a spring moment that is less than the weight moment of the ramp assembly when the ramp assembly is in one or more lowered operating positions.

11. (Original) A dock leveler according to claim 9, wherein the ramp assembly has a weight moment and the shape of the upper cam surface is configured to provide a spring moment that is greater than the weight moment of the ramp assembly at least as the ramp assembly rotates above the operative position.

12. (Original) A dock leveler according to claim 11, wherein the shape of the upper cam surface is configured to provide a spring moment that is approximately equal to the weight moment of the ramp assembly when the ramp assembly is in the stored position.

13. (Previously Presented) A dock leveler according to claim 9, wherein the one or more lowered operating positions are in a generally horizontal working range, the dock leveler has a net moment which can vary as the ramp assembly rotates, and the net moment is relatively constant in the generally horizontal working range, and the net moment is in the upward direction through a region between the generally horizontal working range and the vertical stored position.

14. (Original) A dock leveler according to claim 13, wherein the net moment is approximately zero at a position between the vertical stored position and the one or more operative positions.

15. (Original) A dock leveler according to claim 13, wherein the generally horizontal working range includes positions where an end of the ramp assembly is about eight inches above horizontal to a position where the end of the ramp assembly is about eight inches below horizontal.

16. (Previously Presented) A counterbalance assembly for a mechanically-operated, vertically-storing dock leveler having a rotating ramp assembly, comprising:

ramp means configured to pivot generally about one end of the ramp means;

tension means for counterbalancing the ramp means of a dock leveler, wherein the tension means has a first end and a second end;

means for fixedly coupling said first end of said tension means to the ramp means at a first anchor point;

means for flexibly coupling said second end of said tension means to a base assembly of the dock leveler at a second anchor point, wherein the first anchor point and second anchor point define a direct line of action; and,

means for camming configured to selectively engage the means for flexibly coupling along a side of the flexibly coupling means when the ramp means is located such that the tension means is deflected away from the direct line of action when the tension means and the tension means is operatively connected to the means for flexibly coupling and the ramp assembly rotates,

wherein counterbalance characteristics of the ramp means change as the position of the ramp means changes and the tension means is deflected away from the direct line of action.

17. (Original) A counterbalance assembly according to claim 16, wherein the tension means is a spring.

18. (Previously Presented) A counterbalance assembly according to claim 17, wherein the means for fixedly coupling said first end comprises an adjusting bolt and a spring anchor bracket, and wherein the means for flexibly coupling said second end comprises a flexible tensile member chosen from a chain, a band, and a cable.

19. (Cancelled)

20. (Cancelled)

Application No. 10/664,971
Serial No.: 87353.2980
Customer No. 30734

Special Examination Procedures
Amendment After Final
Under 37 C.F.R. § 1.116

21. (Cancelled)

22. (Cancelled)

23. (Cancelled)